

NO IMAGE
AVAILABLE.

DERWENT-ACC-NO: 2003-769538

DERWENT-WEEK: 200373

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Mounting for sights for handgun has
a mounting block with grooved profile and with a
toothed track into which is located the toothed bottom grip of
the sights support bracket

PATENT-ASSIGNEE: APEL GMBH ERNST[APELN]

PRIORITY-DATA: 2003DE-2009678 (June 24, 2003)

PATENT-FAMILY:

PUB-NO	PAGES	PUB-DATE	
LANGUAGE		MAIN-IPC	
DE 20309678 U1		September 25, 2003	N/A
008	F41G 001/16		

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
DE 20309678U1	N/A	
2003DE-2009678	June 24, 2003	

INT-CL (IPC): F41G001/16

ABSTRACTED-PUB-NO: DE 20309678U

BASIC-ABSTRACT:

NOVELTY - A mounting for sights, e.g. telescopic sights, for a handgun has a mounting block secured to the weapon. This has a grooved profile with the base of the groove provided with a transverse grooves. The block is secured to the weapon by a number of threaded fasteners with the heads of the fasteners set into the hollow profile of the support bracket for the

Best Available Copy

sights. This has a cup shaped upper profile (4) to hold the sights and a hollow (6) base with two bottom grips (8) which are set into one of the grooves of the mounting block.

USE - Sights for handgun

ADVANTAGE - A simple precision mounting with adjustment

DESCRIPTION OF DRAWING(S) - The drawing shows a cross section of a sights support bracket.

Cup shaped upper part of sights support bracket 4

Hollow centre of bracket 6

Grip teeth to locate into grooved support track 8

CHOSEN-DRAWING: Dwg.1a/5

TITLE-TERMS: MOUNT SIGHT MOUNT BLOCK GROOVE PROFILE TOOTH
TRACK LOCATE TOOTH
BOTTOM GRIP SIGHT SUPPORT BRACKET

DERWENT-CLASS: Q79

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N2003-616487